

# Enhanced



MSA the first  
EN 403:2004

## S-CAP

### [ Hood for Escape from Fire ]

It has been proven that most victims during dramatic circumstances due to a fire do not get injured by heat or flames but from smoke and gases. S-CAP is an escape hood especially designed to protect persons endangered by smoke and gases generated by fires. The most dangerous of them is carbon monoxide. S-CAP provides an effective protection for eyes, head and especially the respiratory tract, and thus persons can rescue themselves with little risk.

#### [ Safe Protection ]

The smoke hood S-CAP features a clearly visible bright yellow hood fitted with a wide lens allowing a large field of vision. Inside the hood, a nose cup gives a perfect adaptation to a wide variety of head and face sizes and is directly connected to a multipurpose filter with a broad protection range, including carbon monoxide. For a better respiratory comfort, the hood is also equipped with an exhalation valve.

The adjustable head harness located on the outside of the hood is directly attached to the nose cup. Once tightened, the hood fits the head closely.

The hood material, as well as the harness and the lens, are resistant against heat and short flame contact.

#### [ Improved Performance ]

The new S-CAP has seen its performance improved with the addition of a light cotton neck seal, without affecting the ease of donning, even for persons wearing spectacles. This high level of performance exceeds by far the requirements of the revised European standard EN 403:2004.

#### [ Immediately Operational ]

The protection with S-CAP is effective within seconds and does not require any other specific procedure.

The filter is designed for a rated service time of 15 minutes, depending on the concentration of the contaminants. This time is adequate for escape from buildings under normal conditions. The smoke hood is designed to be used only once. This way, the wearer is assured of the full performance capability of the filter.

#### [ Applications ]

S-CAP can be used also by the rescue teams to assist in the evacuation of people, even if unconscious. As an additional measure of preventive fire protection, S-CAP can increase the safety in residential areas, hospitals, retirement homes, hotels, office building, or meeting rooms.



### [ Easy Donning ]

S-CAP is protected and stored in a vacuum-sealed aluminised foil bag from which it is taken only prior to donning. No further preparations are required. The donning procedure is illustrated on the foil bag. After tearing open the foil bag, the hood is taken out, pulled over the head, the nose cup is fitted over nose and chin, and then the hood is adjusted using the head harness.

### [ Packing Options ]

#### Fireman's Pack

A solid carton contains three S-CAPs in foil bag, each in a metal can. With the carrying grip located off-centre, two cartons can be carried with one hand. The test date is on top of the carton. **Dimensions** approx. 40.5 x 22.5 x 14 cm [H x W x D]. **Weight** approx. 3.1 kg.

#### Cardboard Box

The cardboard box is sealed. The permissible storage life is indicated on the outside.

**Dimensions** approx. 28.5 x 15.5 x 11.5 cm [H x W x D].

#### Wall Box

A two-part plastic box, suitable for wall mounting, contains one smoke hood in its foil bag. The box has a lead seal. The permissible storage life is indicated on the outside. A short instruction on a luminescent label is on the box.

**Dimensions** approx. 28.5 x 15.5 x 12.5 cm [H x W x D].



Wall Box

### [ Features and Benefits ]

- Easiest donning
- Simple and quick handling
- Safe protection of breathing, eyes and head
- Also suitable for persons wearing spectacles
- Large field of vision
- High performance filter
- Low breathing resistance

### [ Technical Data ]

Protection range: The filter fitted on the S-CAP smoke hood protects against numerous contaminants. It removes toxic and eye-irritating fire smoke and gases from the inhaled air, such as carbon monoxide, acrolein, hydrogen chloride, hydrogen cyanide, sulphur dioxide and particles of harmful substances [P2].

*Like any filtering device, the S-CAP should only be used in areas where there is an adequate level of oxygen, as required by local regulation.*

<b>Material:</b>	Hood: Coated PVC
	Neck Seal: Cotton
	Lens: PET
	Inner mask: NR natural rubber, grey
<b>Filter:</b>	Multi Purpose Filter [CO, gases from fire & particles P2]
<b>Weight:</b>	approx. 540 g [ready for use]
<b>Size:</b>	one universal size
<b>Service time:</b>	min. 15 minutes [rated service time]
<b>Breathing resistance:</b>	Inhalation resistance approx. 1.2 mbar Exhalation resistance approx. 0.5 mbar
<b>Storage life:</b>	Factory sealed in foil bag under proper storage conditions. Maintenance-free for 4 years. Thereafter, testing is required. Max. shelf life: 10 years [4 + 4 + 2 years]. Life for S-CAP stored on vehicles: max. 8 years
<b>Approvals:</b>	EN 403:2004

### [ Ordering Information ]

10064644	S-CAP in cardboard box
10064645	S-CAP in wall box
10064646	S-CAP in fireman's pack [pack of three]

#### Your direct contact:

#### MSA Europe Regional Head Offices [www.msa-europe.com]

**Northern Europe**  
MSA Nederland B.V.  
Kernweg 20, NL-1627 LH Hoorn  
Phone: +31 [229] 25 03 03  
Fax: +31 [229] 21 13 40  
E-Mail: info@msaned.nl

**Central Europe**  
MSA AUER GmbH  
Thiemannstrasse 1, D-12059 Berlin  
Phone: +49 [30] 68 86-555  
Fax: +49 [30] 68 86-15 17  
E-Mail: info@auer.de

**Southern Europe**  
MSA Italiana S.p.A.  
Via Po 13/17 - I-20089 Rozzano [MI]  
Phone: +39 [02] 89 217-1  
Fax: +39 [02] 8 25 92 28  
E-Mail: info-italy@msa-europe.com

**Eastern Europe**  
MSA AUER GmbH  
Thiemannstrasse 1, D-12059 Berlin  
Phone: +49 [30] 68 86-25 99  
Fax: +49 [30] 68 86-15 17  
E-Mail: mee@auer.de

Subject to change without notice.  
ID 10-201.2 GB/1./C/05.05/HH

