

Microgard 2000 STANDARD


סרבול למיגון בפני נתזי נוזל וחלקיקים גדולים מ 1 מיקרון

תקנים:



תיאור טכני:

חומר עיקרי: אריג רב שכבתי נושם עם תפרים מחוזקים



מאפיינים:

כיסוי ראש

כיווצי גומי בשרוולים, בקצות המכנס ובמותניים
רוכסן דו כיווני עם כיסוי נגד נוזלים,
טבעת לאגודל
אנטיסטאטי

Fabric Performance



Microporous PE
Laminate

EN14325 Fabric Physical Tests

EN 530 Abrasion	> 100
EN ISO 7854 Flex Cracking	> 40,000
EN ISO 9073-4 Tear Resistance (MD)	40.7N
EN ISO 9073-4 Tear Resistance (CD)	18.6N
EN ISO 13934-1 Tensile Strength (MD)	108.1N
EN ISO 13934-1 Tensile Strength (CD)	48.3N
EN 863 Puncture Resistance	8.2N
EN ISO 13938-1 Burst Resistance	184.1kPa
EN 13274-4 Resistance to ignition	✓
EN 13274-4 Method 3 Resistance to flame	

Specialist Tests

EN 1149-1 Anti-static	✓
BS EN 20811 Hydrostatic Head (water pressure test)	> 200cm
EN533 Limited Flame Retardancy	
EN 368 Repellence to Liquids - 30% Sulphuric Acid	96.7%
EN 368 Repellence to Liquids - 10% Sodium Hydroxide	96.7%
EN 368 Repellence to Liquids - n-heptane (undiluted)	93.8%
EN 368 Repellence to Liquids - Isopropanol	95.5%
EN 368 Resistance to penetration by liquids - 30% Sulphuric Acid	0%
EN 368 Resistance to penetration by liquids - 10% Sodium Hydroxide	0%
EN 368 Resistance to penetration by liquids - n-heptane (undiluted)	0%
EN 368 Resistance to penetration by liquids - Isopropanol	0%

נתונים טכניים
של האריג

Microgard 2000 STANDARD

Features & Benefits

Protection

Proven barrier to low concentration liquid chemicals, diluted pesticides, liquid & particulate biological hazards

Comfort

Low water vapour resistance (Ret <15*) allows perspiration to escape

Cleanroom performance

Low linting, high barrier fabric and seam technology. Proven barrier to particulates larger than 1µm

Anti-Static

Suitable for use in Ex-Zones

Silicone free

Essential for spray painting critical parts

Optimised body fit

For improved wearer comfort and safety. Finger loops help prevent sleeve movement when working above your head

Durable bound seams

Prevents tearing while increasing particle & liquid protection in this critical area. Passed the EN 468 high level spray test**

Choice of colours

Available in white & green

