

Ultrane 548

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Polyurethane foam
 - **Length (cm)** 22-28
 - **Wrist** Knitted wrist
 - **Colour/Color** Black
 - **Interior finish** Seamless textile support
 - **Exterior finish** Ventilated back
 - **Size / EAN** 6 7 8 9 10 11
 - **Packaging** 1 pair/bag - 12 pairs/bag - 96 pairs/carton
 - **Complementary information** Guaranteed without silicone
- Contains traces of DMF in compliance with occupational exposure limits



PERFORMANCE RESULTS

Certification category 2



3131X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4	0-5	0-4	0-4	A-F (P)
Blade cut resistance		Tear resistance		Impact protection
Abrasion resistance		Puncture resistance		Cut resistance according to ISO 13997

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4	0-4	0-4	0-4	0-4	0-4
Contact heat resistance		Convective heat resistance		Radiant heat resistant	
Burning behaviour		Resistance to small drops of molten metal		Resistance to large quantities of molten metal	

CHEMICAL RISKS

EN ISO 374-1 Type A



U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofurane
I Ethyl acetate

EN ISO 374-1 Type B



X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1 Type C



EN 421



**RADIOACTIVE
CONTAMINATION**

MICRO-ORGANISMS

EN ISO 374-5



**Protection against bacteria,
fungi**

EN ISO 374-5



**Protection against bacteria,
fungi, virus**

VIRUS

EN 511



COLD HAZARDS

PERFORMANCE LEVELS

0-4	0-4	0 or 1
Contact cold resistance		Water permeability
Convective cold resistance		

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONNEL

www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Thin glove: excellent tactile sensitivity
- Absorption of perspiration ensured by the cellular structure of the polyurethane. In addition, the particularly open texture of the specific lining helps improve hand ventilation
- Anatomical shape: close fit for precision

MAIN FIELDS OF USE

Automotive/mechanical industry

- Intricate assembly
- Sorting small parts
- Fitting small screws and fasteners

Electronics

- Assembly of electrical components
- Microprocessor handling

Cosmetics and Pharmaceutical industry

- Cosmetics preparation
- Medicine manufacturing

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the tests performed in the laboratory.
- It is not recommended for persons sensitised to natural latex (glove with elastic wrist).
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.

Storage conditions

Store the gloves in their original packaging protected from heat, light and humidity.

Laundering conditions

Caution : using the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/02/14/0117

- Issued by the notified body nr

0075

C.T.C.- 4 rue Herman FRENKEL - F-69367 LYON CEDEX 07