

MSA

TURBO-FLO

BREATHING APPARATUS



- The Turbo-Flo is an assisted fresh air breathing apparatus approved to EN138.
- Turbo-Flo provides assisted breathing for one or two men over 54m distance.
- Options are available for operation from 240V AC, 110V AC or 12V DC power supply.
- Turbo-Flo is robust, weatherproof (IP54) and reliable, ensuring breathing safety and comfort at all times.



Turbo-Flo

RESPIRATORY PROTECTION - AIR SUPPLIED

User Benefits

Assisted breathing prevents user fatigue, and a built-in overflow valve provides a balanced flow preventing discomfort to the eyes.

Twin breathing hose means that the user can use tools/shovels etc., without impedance.

Simple

Fresh air is blown along supply hose to one or two users as required, with varying supply lengths from 9-54 metres each.

Approved for use without blower with up to 18m of supply hose.

Automatic Regulation

Air flow greater than 120 l/min is available to the user on "1 Man" selection and at "Min Flow" setting.

The user can then increase the airflow if desired.

When a second user connects to the Turbo-Flo Blower the "2 Man" position is selected and this automatically ensures flows greater than 20 l/min for each user. Again the airflow can be increased from the "Min Flow" setting is required.

Approval

Turbo-Flo is fully approved to EN 138 as an unassisted/assisted fresh air breathing apparatus.



Turbo-Flo Fresh Air Breathing Apparatus

Ordering Information

PART NO	DESCRIPTION
1260006	Fresh Air B.A. c/w 3S Full Facepiece, Twin Breathing tube, Waistbelt assembly and 9 metre hose c/w couplings.
<u>Accessories</u>	
1260009	Turbo-Flo Blower 240V
1260010	Turbo-Flo Blower 12V DC
1260011	Turbo-Flo Blower 110V
1260015	Spike & Clip
1260016	End Filter
1260021	Storage Case for Fresh Air BA
1260018	18 metre Hose c/w couplings
1266000	Hose Connector

Low Maintenance

Simple, easy and inexpensive maintenance. A well proven, long life motor ensures reliable operation, this results in low maintenance costs.

Reliable Construction

Robust design to withstand the rigours of rough usage.
Approved to IP 54.

Turbo-Flo Blower

Highly portable:
Dimensions: 28cm x 24cm x 24cm
Weight: 5.5kg
Three options available:
240V AC, 110V AC, 12V DC.



Turbo-Flo Blower