



ANTISTATIC SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, SILICONE FREE, 300MM LONG, 0.16MM THICK

Premium performance, powder-free, extended cuff nitrile single use glove with antistatic properties (ESD). Extremely strong and high resistance to chemicals.

FEATURES

- > High quality nitrile, soft and durable
- > Palm thickness 0.16mm (6 mil), weight: 9.1g size M
- > High resistance to penetration and projections of many chemicals
- > Extended cuff (300mm length) to protect the forearm
- > Textured finish on fingertips to enhance grip
- > Powder-free, latex free, non-sterile, AQL 1.5
- > Double Chlorinated inside and oustide to offer more comfort, low tack and reduce friction when donning
- Antistatic properties according to EN 16350:2014: vertical resistance 14.5 \times 106 Ω
- > Eliminates static charge buildup to help prevent sparks and flareups in flammable environment
- > Silicone free



SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION





EN 16350:2014



See overleaf for explanation







PRODUCTION INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	_
COLOUR	Black	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00630BB SKG00630BD SKG00630BF SKG00630BH SKG00630BJ SKG00630BL	100 singles per box 10 boxes per case

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for Mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



EN16350:2014 **ELECTROSTATIC PROPERTIES**



FOOD CONTACT DIRECTIVE 2002 / 72 EC



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE A	CHEMICAL Methanol	CODE	CHEMICAL n-Heptane Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	TYPE OF GLOVES	BREAKTHROUGH TIME
B C D	Acetone Acetonitrile Dichloromethane	K L M		А	≥30 min for at least 6 chemicals
E F G	Carbon Disulfide Toluene Diethylamine	N O P		В	≥30 min for at least 3 chemicals
H	Tetrahydrofurane Ethyl acetate	S T		С	≥10 min for at least 1 chemical

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 F: +44 (0)1618774746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M171SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-TX630-1123_1

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)